

Function

 Price group **53**

"C" in 0 position "1" closed, "2" after "3" discharged

low noise and impact-free closing, for neutral, gaseous or fluids

Brass

| Operating position | Description | Function |
|--------------------|--|----------|
| | <p>In normal position - magnetic system without power - its resting seat is closed. Pressure thus builds up in the control chamber, which due to the larger effective membrane surface holds the membrane in "closed" position.</p> <p>In operational position - magnetic system under power - its seat is open, the control chamber discharged and the membrane is held by the medium in "open" position. A minimum pressure difference is required for this operation.</p> | |

Illustration

| | | | |
|--|--|--|--|
| | <p>These valves with secondary discharge are primarily used where a downstream compressed air load should be relieved deenergised.</p> | | |
| | | <p>Cable socked adaptable with solenoid coil E22 by 2 x 180°, with E30 by 4 x 90° repositionable. Both solenoid coils 360° turnable.</p> | |

Dimensions

| DN | G | L | I | M | L1 | L2 | H | S |
|----|---------|------|------|------|------|-------|----|----|
| 15 | G 1/2 | 68.4 | 13.5 | 34.2 | 78 | 100 | 43 | 27 |
| 20 | G 3/4 | 80.4 | 15.5 | 40.2 | 78 | 99.5 | 43 | 32 |
| 25 | G 1 | 94 | 17 | 47 | 86 | 115.5 | 59 | 41 |
| 32 | G 1 1/4 | 112 | 19 | 56 | 86 | 115.5 | 59 | 50 |
| 40 | G 1 1/2 | 132 | 21 | 66 | 99.5 | 143 | 87 | 55 |
| 50 | G 2 | 160 | 24.5 | 80 | 99.5 | 143 | 87 | 70 |

Mounting Accessories

| Illustration | Suitable for valves | Type | Order number | Price |
|--------------|----------------------------------|--------------------------|--------------|-------|
| | G 1/2 + G 3/4 DN 15 and DN 20 | ZGV-10normal D2normal 52 | 616252 | o. r. |
| | G 1 + G 1 1/4 DN 25 and DN 32 | ZGV-10normal D32-62 | 616262 | o. r. |