

Function

Price group **53**

Function "A" normally closed

low noise and impact-free closing, for neutral, gaseous or fluids

Brass

Operating position	Description	Function
	<p>In normal position - magnetic system without power - its resting seat is closed. Pressure thus builds up in the control chamber, which due to the larger effective membrane surface holds the membrane in "closed" position.</p> <p>In operational position - magnetic system under power - its seat is open, the control chamber discharged and the membrane is held by the flow medium in the "open" position. A minimum pressure difference is required for this operation.</p>	

Illustration

Cable socket adaptable with solenoid coil E22 by 2 x 180°, with E30 by 4 x 90° repositionable. Both solenoid coils 360° turnable.

Dimensions									Mounting Accessories				
DN	G	L	I	M	L1	L2	H	S	Illustration	Suitable for valves	Type	Order number	Price
15	G 1/2	68.4	13.5	34.2	72	93.5	43	27		G 1/2 + G 3/4 DN 15 and DN 20	ZGV-10normal D2normal 52	616252	o. r.
20	G 3/4	80.4	15.5	40.2	72	93.5	43	32					
25	G 1	94	17	47	80	109.5	59	41					
32	G 1 1/4	112	19	56	80	109.5	59	50					
40	G 1 1/2	132	21	66	93.5	137	87	55					
50	G 2	160	24.5	80	93	136.5	87	70		G 1 + G 1 1/4 DN 25 and DN 32	ZGV-10normal D32-62	616262	o. r.